FLUKE®

9040 Phase Rotation Indicator

Technical Data

Features

- Large display to easily determine field rotation
- Indication for all three phases
- CAT III 600 V
- Included accessories: test leads and probes, alligator clips
- 2-Year Warranty

Phase Rotation Indicator for industrial applications

The Fluke 9040 Phase Rotation Indicator is a portable handheld instrument designed to detect the rotary field of three-phase systems. With three test leads, this rugged tester easily determines a clockwise or counterclockwise direction.

http://instrumentation.bhd.ca/

FLUKE

Specifications

Environmental

Operating temperature:
0 °C to +40 °C (32 °F to 104 °F)
Pollution degree: 2
Type of protection: IP 40

Mechanical specifications

Size (HxWxD):
124 mm x 61 mm x 27 mm
(4.9 in x 2.4 in x 1.1 in)
Weight: 200 g (0.44 lbs)

Safety specifications

Electrical safety:
IEC 61010/EN 61010,
IEC 61557-7/EN 61557-7
Maximum operating voltage (U_{max}): 690 V
Protection levels: CAT III 600 V to ground

Electrical specifications

Power supply: From unit under test

Determine rotary field direction

Nominal voltage: 40 to 690 V ac
Frequency range (f_n): 15 to 400 Hz
Current Pickup: 1 mA
Nominal test current (in per phase): 1 mA
Warranty: 2 years

Included

3 self-retaining test probes (black)
Alligator Clip
Users Manual

Ordering Information

Fluke-9040 Phase rotation indicator

Visit Website

http://instrumentation.bhd.ca/